

Product Catalogue



R-100


(fixed head pad)

This model is ideal for door openings of 8' wide x 8' high. The model R-100 is a standard dock seal which includes two side pads and one fixed head pad. This option is the most economical way to seal the back of a trailer to a loading dock area. It also provides protection to personnel and cargo while loading and unloading and also provides protection from bad weather, dirt and insect infiltration.




Available options:


- Tapered seals (for incline / decline approach)
- Wedge seals (for wider openings)
- Extra vertical pad height
- Higher head pad
- Protective wear flaps
- Double layer on impact area
- Velcro drop flap
- Extra projection
- Full height yellow guide stripe




Higher head pad




Double layer on impact area



Protective wear flaps



Extra vertical pad height




Wedge verticals




Tapered (incline approach)




Tapered (decline approach)



Velcro drop flap



Extra projection



Full height yellow guide stripe

R-600

(adjustable split curtain)

This model is ideal for door openings of 8' wide x 10' high. The model R-600 includes two side pads and one adjustable head curtain. The adjustable rope and pulley head curtain provides protection for a wide range of truck heights. It also provides protection to personnel and cargo while loading and unloading and also provides protection from bad weather, dirt and insect infiltration.




Available options:


- Tapered seals (for incline / decline approach)
- Wedge seals (for wider openings)
- Extra vertical pad height
- Extra curtain length
- Protective wear flaps
- Double layer on impact area
- Velcro on split curtain
- Extra projection
- Full height yellow guide stripe




Tapered
(incline approach)




Tapered
(decline approach)




Wedge verticals




Extra vertical
pad height




Extra length
curtain




Protective
wear flaps




Double layer
on impact area



Extra projection



Full height yellow
guide stripe



Velcro on
split curtain


R-700

(L-pad with adjustable split curtain)

This model is ideal for door openings of 10' wide x 10' high. The model R-700 includes two side pads and one adjustable head curtain. The L shape vertical seals from the side of the trailer rather than on the door frame. The adjustable rope and pulley head curtain provides protection for a wide range of truck heights. It also provides protection to personnel and cargo while loading and unloading and also provides protection from bad weather, dirt and insect infiltration.

Available options:


- Tapered seals (for incline / decline approach)
- Extra vertical pad height
- Extra curtain length
- Protective wear flaps
- Double layer on impact area
- Velcro on split curtain
- Extra projection
- Full height yellow guide stripe
- Bottom draft flap




Tapered
(incline approach)




Tapered
(decline approach)




Extra vertical
pad height




Extra length
curtain




Bottom draft flap




Protective
wear flaps




Double layer on
impact area



Extra projection



Full height yellow
guide stripe



Velcro on split
curtain

Dock Accessories



Dock Bumpers



Air Gap Sealer




Strip PVC Door




Dock Lights



Steel Projection Boxes



Wheel Chocks



Vertical Leveler Seal Cushion

Fabric Specs

22 oz. vinyl:

Abrasion resistant, flame retardant, U.V. resistant for long life, rot, mildew and fungus resistant, superior low temperature performance.

40 oz. vinyl:

Abrasion resistant, flame retardant for the life of the fabric, U.V. resistant for long life, rot, mildew and fungus resistant, superior low and high temperature performance, rip stop base textile prevents snags from becoming tears, puncture and tear resistant.

16 oz. Hypalon:

Abrasion resistant, flame retardant, U.V. resistant for long life, rot, mildew, fungus, oil and grease resistant, superior low temperature performance, puncture and tear resistant, non-sticky surface will not attract dust.

40 oz. Hypalon:

Abrasion resistant, flame retardant, U.V. resistant for long life, rot, mildew, fungus, oil and grease resistant, superior low and high temperature performance, puncture and tear resistant, non-sticky surface will not attract dust.

112 oz. Dura-Tex:

Abrasion resistant, flame retardant for the life of the fabric, U.V. resistant for long life, rot, mildew and fungus resistant, superior low and high temperature performance, rip stop base textile prevents snags from becoming tears, puncture and tear resistant, extremely durable.

Available Fabrics

	Tear (lb) (w x f)	Tensile (lb / inch)	Adhesion (lb / inch)	Cold Crack (1/8 Mandrel)	Abrasion Resistance	Flame Resistance
22 oz. Vinyl	130 x 95	430 x 390	17	-35°C / -31°F	>300 cycles	Pass
40 oz. Vinyl	150 x 140	461 x 443	12	-60°C / -76°F	>10,000 cycles	Pass
16 oz. Hypalon	250 x 240	400 x 350	15	-46°C / -50°F	>3000 cycles	Pass
40 oz. Hypalon	250 x 250	400 x 350	10	-46°C / -50°F	>4,500 cycles	Pass
112 oz. Dura-Tex	600 x 450	800 x 800	10	N/A	>25,000 cycles	Pass

Product Catalogue

